


HOTSOAK 79


HOTSOAK SERIES MODEL # AI6036SVHS

















Rough-In Plumbing

SPECIFICATIONS:

GENERAL SPECIFICATIONS:

58 7/8" x 35 1/8" x 20 1/2" **Tub Size**

150 cm x 89 cm x 52 cm

Bathing Well 42" long

23 1/2" wide

19 1/2" interior depth

Shipping Weight 171 lbs. / 78 kg Tub Weight Filled 617 lbs. / 280 kg **Tub Only Weight** 136 lbs. / 62 ka Gallons to Overflow 63 gal. / 2389 L

ELECTRICAL SPECIFICATIONS:

1/15 HP; 1.3 AMP; 110V 1.5 kW; 12.5 AMP; 110V Heater 20 AMP; 110V, separate circuit Requirements required protected w/ Class A GFCI

STANDARD EQUIPMENT:

Aquatic Quality Features:

- 1.5 kW Inline Maintenance Heater - Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- Slip Resistant Floor
- 2 Arm Rests
- Extra Deep and Long Bathing Well
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty

OPTIONAL EQUIPMENT:

- Chromatherapy LED Lighting*
- Comfort Pillow Oval or Rectangle
- **Bolt-On Grab Bars**
 - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Factory Installed Rigid ABS Tile Flange
- **Optional Pump Location**
- Color Matched Acrylic Skirt
- **Premium Colors**

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

Fax-On-Demand Document #1254



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation www.aguaticwhirlpools.com 800,555,5324 and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work,